





ICAR - INDIAN INSTITUTE OF RICE RESEARCH

(Formerly Directorate of Rice Research)

Rajendranagar, Hyderabad - 30: Telangana Phone No's: 040-24591201: FAX: 040-24591217



F.No.6-1-35/Dyad (dual) Thermal cycler/DBT-Marker-assisted...in rice/RMS/P&S/16-17 /3902

Date: 15-03-2017

BY REGD.POST

ENQUIRY NO: 123(01-27)

TENDER FOR :" Dyad (dual) Thermal cycler"

DUE DATE : 25/03/2017

To

Sub: Procurement of Dyad (dual) Thermal cycler (1 No)- Reg.

Dear Sir,

Tenders are invited for Procurement of Dyad (dual) Thermal cycler (1 No) as per the following specifications Copy Enclosed.

You are therefore, requested to kindly submit your Tender for the above said items to the Senior Administrative Officer, Indian Institute of Rice Research, Rajendranagar, Hyderabad 500 030 by Post/Courier.

NOTE: LIMITED TENDERS BY POST ARE ONLY ACCEPTED

P.T.O

TERMS & CONDITIONS

- 1. The last date for submission of Tenders is 25-03-2017 at 02:30 PM.
- 2. Tenders should be submitted only by POST / COURIER in a sealed cover addressed to Senior Administration Officer, Indian Institute of Rice Research, Rajendranagar, Hyderabad – 500030 so as to reach by at 02:30 PM in the closing day. Delay on account of postal / other will not be the responsibly of the IIRR. The cover containing Tender should invariably be superscribed separately "Tenders are invited for Dyad (dual) Thermal cycler (1 No)".
- 3. 2% of EMD drawn in favour of Director, IIRR, Rajendranagar, Hyderabad on estimated cost to be enclosed along with the Tender.





- 4. The successful bidder has to furnish an amount, equivalent to 10 % of the order value as security Deposit which will be refunded / returned only after satisfactory completion of the contractual obligations including warranty.
- 5. No advance payment will be made. Payment will be made through on-line after satisfactory installation/certification of the concerned Officer. Please furnish the following details:

Account Name : Account Number : Account Type : MICR Code : Branch : IFSC Code : Bank Address : :

- The rates quoted should be net payable for each item for delivery at the Institute at the address given above (inclusive of all taxes, packing forwarding, transport, insurance and excluding rebate/discount etc.)
- 7. This institute is not in a position to supply and "D" or "C" forms
- 8. While quoting the rates please mention the following:

Approximate time for supply of stores from the date of placing order

Tender which does not conform to the above terms and conditions will not be considered. The Director, IIRR reserves the right to accept or reject any or all Tenders without assigning any reasons thereof.

Yours faithfully,

Asst. Administrative Officer

Copy to

> Dr. B. Sailaja, Scientist, GIS - to be placed in IIRR Website/Central Procurement Portal

Specifications of Equipment to be purchased under DBT sponsored project entitled "Marker-assisted introgression of yield enhancing genes in rice to increase yield potential in rice" Revined Speakodons

Dyad (dual) Thermal cycler (1 No.)

- 1. Instrument should be with capacity of 2 x 96-wells. The equipment can have a 16 configuration of two separate thermal cyclers connected to a common control unit or two separate thermal cyclers can also be supplied to run two separate programmes on 2 x 96 wells as part of the Dyad (dual) thermal cycler. The wells should be capable of accommodating 0.2 ml tubes; 12-strip wells; 96-well plates
- 2. The instrument should be certified/licensed for use in PCR/thermal cycling
- 3. Control system should be digital and should have LCD/LED touch screen.
- Reaction volume range of 10-100 μl along with Speed controls like Fast and standard
- Temperature range of 0 to 100.0 °C with Accuracy levels of ±0.25°C (35°C to 99.9°C).
- 6. Temperature uniformity should be < 0.5 °C (20 sec after reaching 95 °C).
- 7. Instrument should be able to Auto re-start (after power outages) & should have sleep mode option to control in HH:MM:SS mode.
- 8. Program should have overwrite protection & should have infinite hold facility.
- 9. The system should be capable of running in both Fast and Standard modes
- 10. Peak Block Ramp Rate (i.e. under Fast mode) required is 3.0°C/Sec.
- 11. Sample Ramp Rate at Standard mode: ± 1.5°C/sec.
- 12. High Thoughput-Compatibility of different blocks may be available which should not require any tools to fix the kit (optional)
- Internal memory should be available to save data along with option to use USB.
- Power requirement: 100-240V, 50-60 Hz Max: 950 VA
- 15. Should be essentially supplied with a 3 KVA UPS of standard make to provide uninterrupted power supply to the equipment (i.e. both the thermal cyclers) for at least 3 hours (when programs are running in both the blocks)
- 16. System should be preferably supplied with a branded HP Laptop computer (Intel core i5 processor; 8GB RAM, HDD: 1TB; Screen: 14 inches; OS: MS Windows 10, Office 2010 or 2007) for data capture, storage and retrieval and a branded multi-function laser printer for data documentation. The quote for the laptop and printer should be given separately.
- 17. Warranty for 2 years (compulsory) plus 2 years free AMC (optional).
- 18. A certified compliance statement (sample given below) wherein all the claims and specifications about the instrument should be supported by a printed and authentic technical literature.

Any additional remarks, if any
additional details and improved specifications, if